



LIFELAMP 16 WATT DIMMABLE LED




ITEM DLS16WBB27K (50/Ctn)

ITEM DLS16WBB50K (50/Ctn)

L(mm) 141 (-0+5) D(mm) 75 (-0+3)



Performance Parameters	
Supply Voltage AC (V):	120V
Base Type:	E26
Input Frequency (Hz):	60Hz
Input Current (mA):	145
Test Conditions	0-70°C
Input Power (W):	16 Watt +/- 5%
Power Factor (λ):	≥0.9
Beam Angle:	180° +/- 5%
Dimmable	yes
Dimming Range:	1% - 100%
	<i>min / spec / max</i>
Color Temperature (K):	2700 / 5000
Luminous Flux (lm):	1600 / 1900 +/- 5%
Luminous Efficiency (lm/W):	96.6 / 96.9
Color Rendering Index (Ra):	>80
Duv	0.000±0.006
Lumen Maintenance @ 6000 Hours	
	@ 83 Degree C Case Temp: 97.93% of Initial Lumens
	@ 103 Degree C Case Temp: 97.11% of Initial Lumens

Safety Characteristics

Certification: CUL FCC

UL Wet Location Else

UL and FCC Standard:

UL1993 UL8750 Part 15

Lifetime and Operating Temperature		<i>spec / max</i>
L70 Life Time (Approx hrs)		50,000
Operating Temperature Range		-20 to 40°C

These are extraordinary waterproof LED bulbs warrantied for 5 years. Every bulb is shipped with the exclusive LifeLamp socket seal gasket which prevents water spray from reaching the LifeLamp base.