



LIFELAMP 6 WATT BROADBEAM LED




ITEM DLS6WBB27K (40/Ctn)

ITEM DLS6WBB50K (50/Ctn)

L(mm) 110+2.5 D(mm) 60+2



Performance Parameters	
Supply Voltage AC (V):	120V
Base Type:	E26
Input Frequency (Hz):	60Hz
Input Current (mA):	50
Test Conditions	0-70°C
Input Power (W):	6 Watt +/- 5%
Power Factor (λ):	> 0.6
Beam Angle:	230° +/- 5%
Dimmable:	yes
Dimming Range:	1% - 100%
	<i>min / spec / max</i>
Color Temperature (K):	2700 / 5000
Luminous Flux (lm):	540/ 600 +/- 5%
Luminous Efficiency (lm/W):	80
Color Rendering Index (Ra):	>80
Duv	0.000±0.006
Lumen Maintenance @ 6000 Hours	
	@ 83 Degree C Case Temp: 98.85% of Initial Lumens
	@ 103 Degree C Case Temp: 97.68% of Initial Lumens

Safety Characteristics

Certification: CUL FCC

UL Wet Location Else

UL and FCC Standard:

UL1993 UL8750 Part 15

Lifetime and Operating Temperature		<i>spec / max</i>
L70 Life Time (Approx hrs)		50,000
Operating Temperature Range		-20 to 40°C

These are extraordinary waterproof LED bulbs warrantied for 5 years. Every bulb is shipped with the exclusive LifeLamp socket seal gasket which prevents water spray from reaching the LifeLamp base.